

## LIGHTING TECHNOLOGY



	PAGE
LED-BALL POINT PEN	522
EMERGENCY LAMPS	522
HEAD LAMPS	522
INSPECTION LAMPS	522 - 523
LED HAND LAMPS	523 - 524
WORKSHOP LAMPS	524
FLASHLIGHTS	525
ACCESSORIES FOR FLASH LIGHTS	525
FLASH LIGHTS WITH CABLE REELS	526
WORK LAMPS	526 - 527
WORK LAMPS WITH TRIPODS	527 - 529
ACCESSORIES FOR WORK LAMPS	529

i



## LIGHTING TECHNOLOGY POWER STRIPE LED

# Construction LEDMAX POWER STRIPE LED battery operating lamp

### **LED Cordless workshop lamp**

- ·Ideal for very long network independent working
- •6 Watt Citizen Power LED
- •Housing 180° foldable
- ·Housing body covered with high quality rubber
- •Weatherproof protection IP64
- Shock and impact resistant
- •Revolving hooks for suspending
- Magnetic
- ·With control LED to discharge
- •Includes automatic turn off charging station
- •3 hours charging time
- •3 hours lamp duration
- •Impact resistant Polycarbonate housing

#### Technical data

Capacity: Light source: Luminosity: Rechargeable battery: Battery type: Capacity:

Capacity: Charging voltage:

Working temperature: Weight:

illumination time 3 hours 6 W POWER Stripe LED 420 lumen 3,6 V / 3600 mAh Li-polymer 6 Watt AC 100-240 V ~ 50 / 60 Hz DC 12-24 V

DC 12-24 V -5° / +45° 0.50 kg















## Important basic concepts of light engineering Technical data on the torch market are confusing and often not comparable

#### lumens



#### Luminous flux in lumens (Im)

The luminous flux is the most important term to characterise the output of a lamp. It describes the actual light quantity or light energy emitted from a light source. What is actually measured? Some manufacturers specify

the luminous flux of the LED or light bulb and in the process don't mention that this is significantly reduced in the reflector/lamp head (sometimes by more than 30%). Our luminous flux values

are values measured with spectrometers, which the lamps emit with new batteries from the reflectors.

#### lux



#### Illuminance in lux

This value indicates how intensely a surface is illuminated. This comes from photography and light architecture. There are clear specifications as to what illuminance work places or supermarket halls have to have.

The illuminance is measured with luxmeters.

#### candela



### Light intensity in candela (ca)

The light intensity denotes - in a simplified form - the intensity of the light output. This is dependent on the luminous flux (quantity of light) and the output angle of the light. Example: 5 mm LEDs have different beam angles, e.g. 10 and 120°.

Despite the same light energy the 10° diode has

12 times more light intensity as the 120° diode. The same quantity of light is distributed once to 10 and once to 120°. 10 m away a 10° diode only operates at an angle of 10°, whereas the 120° diode operates at the same light at an angle of 120°. The light intensity is the designation for the part of the luminous flux emitted in a certain direction.

#### LED (Light Emitting Diode)

Light emitting diodes are microstructural solid states and completely unsusceptible to vibrations. They last 1000 times longer than conventional light bulbs, unlike halogen lamps they produce no shades, hardly produce warmth and use less electricity. LEDs contain no harmful filling gases and produce no ultraviolet rays.

#### Power consumption

The power consumption of a lamp and their bright performance are two completely different things. The fact that a lamp uses a lot of energy by no means that they produce a lot of light. The largest part of the energy is still moved in warmth.

This is also applies to LEDs a high efficient 1 watt diode which can supply more light than one low quality 5 watt diode.

#### Light efficiency



100 Hours\*









<sup>\*</sup> In this juncture, it is about calculated average values. According to type of the lamp abnormalities can occur. \*\* With 15 / 25 watt lamps. According to type of the lamp abnormalities can occur. \*\*\* After 100.000 working hours LEDs still shine with 50% of the brightness.



### Light engineering lines

#### LED ball point pen





Flash lights



**Emergency lamps** 



LED hand lamps



Work lamps



Head lamps



Workshop lamps



Cable reels



### IP Protection class identification mark

The housing protection degree, is fixed as the standards IEC 529 or DIN EN 60 52 which contain several different protection types. The illustration below shows an overview of the protection classes which are represented as follows.

- If for the designation the 1st or 2nd place is not important, it is replaced by X.
- Perhaps 3rd place Additional touch protection / perhaps 4th place Supplementary character
- Representation in accordance to DIN VDE 0470, DIN EN 60 529, IEC 60529

### IP Protection class definition

1. ref. number	range of protection
0	no touch protection, no protection against compact foreign objects
1	protection against extensive touch with hand protection against foreign objects Ø >50 mm
2	protection against touch with fingers protection against foreign objects Ø >12 mm
3	protection against touch with tools, wire etc with Ø >2,5 mm protection against foreign objects Ø >2,5 mm
4	protection against touch with tools, wire etc with Ø >1 mm protection against foreign objects Ø >1 mm
5	protection against touch protection against dust deposit inside
6	complete protection against touch protection against entry of dust

2. ref. number	range of protection
0	no protection against water
1	protection against vertical falling raindrops
2	protection against angular falling raindrops (every angle up to 15° to vertical)
3	protection against water in every angle up to 60° to vertical
4	protection against splash water from all directions
5	protection against jet of water (blast pipe) every angle
6	protection against temporary flooding
7	protection against ingress of water during temporary immersion
8	protection against pressure water during constant immersion



#### LED BALL POINT PEN

#### 4 in 1 LED ball point pen

- ·Ball point pen
- •LED lamp
  •Laser pointer
- · Handheld pencil
- ·Clip for the breast pocket
- Approx. 60 hours lamp duration Includes 4 x LP 41 button cell
- •Impact proof housing



	L mm	D mm	9	
10010	150.0	13.0	110	

#### 2 in 1 LED ball point pen

- Ball point pen
   LED lamp
- •Focus lens
- ·Clip for the breast pocket
- Approx. 60 hours lamp duration Includes 4 x LP 41 button cell
- Impact proof housing



	L mm	D mm	9	
10012	130.0	13.0	100	

### EMERGENCY LAMPS

#### **Emergency light**

- •In the event of an emergency
- •9 warning functions
- Magnetic
   With suspension device
- •Ingress protection according to IP54
  •Includes 1 x CR 123 battery
- Impact-resistant



#### Technical data:

Luminosity 13.000 mcd CR 123 Battery: -10° to +40°C Working temperature:


	Ø mm	H mm	g	
550.1360	107	35.0	200	




#### **HEAD LAMPS**

#### LEDMAX CREE Power LED headlamp with focus

- •3 Watt CREE Chip Power LED
- Luminous flux 140 Lumen Headlight range of up to 100 meters
- Zoom from spot to flood light
   Multifunctional-button with 4 modes: On/Off / 5W / 3W / Blink
- Adjustable front and head band for comfort and to stay in place
  • Lamp can be additionally tilted in 5 click stops
- Weatherproof protection IPX3
   3 hours lamp duration
- •Includes 3 x AAA 1,5V batteries








#### Technical data:

max. 100,0 m Headlight range: Luminosity: 3 W Working temperature: 0°/+40°C

	D mm	H mm	L1 mm	L2 mm	g	
550.1238	30.0	40.0	65.0	30.0	80	





#### LEDMAX CREE-Power LED torch

- •Ideal for smock and shirt pockets
- •1 Watt CREE Chip LED •85 Lumens luminous flux
- •25 m headlight range
- Ingress protection according to IPX3Clip for the breast pocket

- •5 10 hours lamp duration •Includes 2 x AA 1,5 V batteries
- Ultra light and impact resistant aluminium housing



#### Technical data:

max. 25,0 m Luminosity: 1 W 0°/+40°C Working temperature:

	L mm	D mm	9	
150.4370	140.0	16.0	50	

#### Flexible UV inspection lamp

- •LED UV lamp
- Flexible shaft
   Localizes leaks in air conditioning systems
- Clip for the breast pocket
   Approx. 60 hours lamp duration
- Includes 3 x AAAA batteries
- Impact proof housing



	L mm	D mm	Spare bulb	g	
550.1165	450.0	7.5	550.1167	150	

3

#### Flexible inspection set

- ·Halogen lamp
- Flexible shaftIncludes flexible fibreglass attachment
- Clip for the breast pocket
   Includes single lamp bulb
- · Approx. 60 hours lamp duration
- •Includes 2 x LR 03 button cell + 2 x 1,5 V AAA batteries
- Impact proof housing



	L mm	B mm	H mm	Spare bulb	9	
550.1160	210.0	150.0	25.0	550.1161	230	

#### Flexible inspection lamp with extension

- · Halogen lamp
- Flexible shaft
- Includes extension
- Approx: 60 hours lamp duration
- Includes 2 x AA batteries
- Impact proof housing



	L mm	D mm	Spare bulb	g	
550.1185	400.0	5.0	550.1187	120	

#### Illuminated inspection mirror

•LED lamp

550.1138

- Flexible shaft
- •Adjustable by thumb pressure to 90°
- Approx. 60 hours lamp durationIncludes 2 x AA batteries

600.0

40.0

·Stable plastic housing



38 x 73

550.1139 280



#### **LED HAND LAMPS**

#### MONSTER CREE-Power LED lamp 1000

- · Ideal for network independent working
- •On/off mode
  •1 x CREE LED light
- •1,000 lumens luminous flux
- •300 m range
- •Scratchproof with hard-coat anodising
- •shockproof and waterproof •splashproof in accordance with IPX8
- •includes 1 x 3.7V lithium battery (BRC 18650) •shockproof aluminium housing

- incl. belt clip
   incl. automatically switch off loading station



Technical data:

Light source 1 x Cree Power LED Headlight range: max. 300,0 m Luminosity 1000 lumen Rechargeable battery: 3.7 V / 3000 mAh Battery type: Lithium-ion Capacity: 10 Watt Charging voltage: AC 100-240 V ~ 50 / 60 Hz

DC 12-24 V

Working temperature:	0°/+40°C

	L mm	D mm	Replacement battery	9
150.4360	145.0	45.0	150.4361	115

#### MONSTER CREE-Power LED lamp 5000

- Ideal for network independent working
  •5 lighting modes 3 levels of brightness, SOS and stroboscope
- •5 x CREE LED lights
- •5,000 lumens luminous flux
- •300 m range •digitally controlled for consistent brightness
- Aluminium reflector
- · Clear glass lens
- Scratchproof with hard-coat anodising
- •shockproof and waterproof •splashproof in accordance with IPX8
- •includes 3 x 3.7V lithium battery (26650) •shockproof aluminium housing
- •incl. belt clip
- •incl. automatically switch off loading station



### Technical data:

5 x Cree Power LEDs Headlight range max. 300,0 m 1000 lumer Luminosity 3,7 V / 4000 mAh Rechargeable battery: Battery type: Lithium-ion Capacity: 24 Watt Charging voltage: AC 100-240 V ~ 50 / 60 Hz DC 12-24 V

Working temperature: 0° / +40°C

	L mm	D mm	Replacement battery	g	
150.4365	310.0	62.0	150.4362	365	

#### MONSTER CREE-Power LED lamp 8000

- · Ideal for network independent working
- •5 lighting modes 3 levels of brightness, SOS and stroboscope •7 x CREE LED lights
- - •8,000 lumens luminous flux
- •300 m range
- digitally controlled for consistent brightness
- Aluminium reflector
- ·Clear glass lens
- Scratchproof with hard-coat anodising
   shockproof and waterproof

- splashproof in accordance with IPX8 includes 3 x 3.7V lithium battery (26650)
- ·shockproof aluminium housing
- incl. belt clip
- •incl. automatically switch off loading station



#### Technical data:

Light source: 7 x Cree Power LEDs Headlight range max 300 0 m Luminosity 1000 lumen Rechargeable battery: 3.7 V / 4000 mAh Battery type: Lithium-ion Capacity 35 Watt AC 100-240 V ~ 50 / 60 Hz Charging voltage

DC 12-24 V

Working temperature: 0°/+40°C

	L mm	D mm	Replacement battery	9	
150.4366	320.0	63.0	150.4362	535	

### MONSTER CREE-Power LED lamp 10000

- Ideal for network independent working
- •5 lighting modes 3 levels of brightness, SOS and stroboscope
- •9 x CREE LED lights
- •10,000 lumens luminous flux

  - •300 m range •digitally controlled for consistent brightness
  - Aluminium reflector
  - · Clear glass lens
  - · Scratchproof with hard-coat anodising
  - shockproof and waterproof
  - •splashproof in accordance with IPX8
  - •includes 3 x 3.7V lithium battery (26650) shockproof aluminium housing
  - •incl. belt clip
  - ·incl. automatically switch off loading station



Working temperature:

9 x Cree Power LEDs Light source Headlight range max. 300,0 m 1000 lumer Luminosity 3,7 V / 4000 mAh Rechargeable battery: Battery type: Lithium-ion Capacity: 32 Watt Charging voltage AC 100-240 V ~ 50 / 60 Hz

	L mm	D mm	Replacement battery	g	
150.4367	325.0	78.0	150.4362	665	

DC 12-24 V

0°/+40°C

4

5

6

7 8

9 10

11 12

13 14

15

16

17 18

19

20

21

22

23

24

25

26

27



#### MONSTER CREE-Power LED lamp 13000

- Ideal for network independent working
- •5 lighting modes 3 levels of brightness, SOS and stroboscope •12 x CREE LED lights
- •13,000 lumens luminous flux
- •300 m range
- digitally controlled for consistent brightness
- Aluminium reflector
- ·Clear glass lens
- Scratchproof with hard-coat anodising
- shockproof and waterproof
- splashproof in accordance with IPX8 includes 3 x 3.7V lithium battery (26650)
- ·shockproof aluminium housing
- incl. belt clip
- •incl. automatically switch off loading station



#### Technical data:

Light source 12 x Cree Power I FDs Headlight range max 300 0 m Luminosity 1000 lumen Rechargeable battery: 3.7 V / 4000 mAh Battery type: Lithium-ion Capacity 36 Watt

Charging voltage AC 100-240 V ~ 50 / 60 Hz

DC 12-24 V 0° / +40°C

Working temperature:

	L mm	D mm	Replacement battery	g	
150.4368	415.0	89.0	150.4362	1000	

#### **WORKSHOP LAMPS**

#### **LEDMAX LED Cordless work lamp**

- · Ideal for very long network independent working
- •30 Power Chip LEDs
- Housing body covered with high quality rubberWeatherproof protection IP54
- Shock and impact resistant
- Revolving hooks for suspending
- Magnetic
- With control LED to discharge
- Includes automatic turn off charging station
- •4-5 hours charging time •9 hours lamp duration
- •Impact resistant Polycarbonate housing



#### Technical data:

Capacity: illumination time 9 hours Light source 30 + 1 W LED Luminosity 800 Lux Rechargeable battery: 3 7 V / 3500 mAh Battery type Lithium-ior Capacity 1.2 Watt Charging voltage: AC 100-240 V ~ 50 / 60 Hz

DC 12-28 V Working temperature: -5° / +45°

	L mm	D mm	9	
150 4240	280.0	50.0	590	
150.4240	280.0	50.0	590	

#### LEDMAX SMD-Cordless work lamp

- · Ideal for very long network independent working
- •30 SMDs
- Housing body covered with high quality rubber
- Weatherproof protection IP54
   Shock and impact resistant
- Revolving hooks for suspending
- Magnetic
- With control LED to discharge
- · Includes automatic turn off charging station
- •4-5 hours charging time •9 hours lamp duration
- •Impact resistant Polycarbonate housing



#### Technical data:

Capacity illumination time 9 hours Light source 30 SMDs 95 lumen Luminosity: 3,7 V / 3500 mAh Rechargeable battery: Battery type: Lithium-ion 1.2 Watt Capacity:

AC 100-240 V ~ 50 / 60 Hz Charging voltage: DC 12-28 V

Working temperature: -5° / +45°

	L mm	D mm	g	
150.4330	280.0	50.0	590	

### LEDMAX SUPER BRIGHT LED-Cordless work lamp

- Ideal for very long network independent working
- •3 + 1 W SUPER BRIGHT LED's
- Housing body covered with high quality rubberWeatherproof protection IP54

- •Shock and impact resistant •Revolving hooks for suspending
- Magnetic
- With control LED to discharge
- Includes automatic turn off charging station
- •4-5 hours charging time
- •4-5 hours lamp duration
- Impact resistant Polycarbonate housing



#### Technical data:

illumination time 4-5 hours Light source 3 + 1 W SUPER BRIGHT LEDs Luminosity 2500 Lux Rechargeable battery: 3 7 V / 3500 mAh Battery type Lithium-ion Capacity 2.5 Watt Charging voltage: AC 100-240 V ~ 50 / 60 Hz

DC 12-24 V Working temperature: -5° / +45°

D mm L mm g 150.4340 645 280.0 50.0

#### LEDMAX STRIPE LED-Cordless work lamp

- · Ideal for very long network independent working
- •2.5 W Stripe LED

Magnetic

- Housing body covered with high quality rubber
- Weatherproof protection IP54
   Shock and impact resistant

- Revolving hooks for suspending
- With control LED to discharge
- Includes automatic turn off charging station4-5 hours charging time
- 4-5 hours lamp duration
- Impact resistant Polycarbonate housing



#### Technical data:

illumination time 4-5 hours Capacity Light source 2,5 W Stripe LED Luminosity: 180 lumen 3,7 V / 3500 mAh Rechargeable battery: Lithium-ion Battery type: Capacity: 2.5 Watt

AC 100-240 V ~ 50 / 60 Hz Charging voltage:

DC 12-24 V

Working temperature -5° / +45°

	L mm	D mm	9	
150.4350	280.0	50.0	645	

### LEDMAX POWER STRIPE LED Cordless working lamp,

- Ideal for very long network independent working
- •6 Watt Citizen Power LED
  •Housing 180° foldable
- Housing body covered with high quality rubber
- Weatherproof protection IP64
   Shock and impact resistant
- Revolving hooks for suspending
- Magnetic
- •With control LED to discharge
- · Includes automatic turn off charging station
- •3 hours charging time
- •3 hours lamp duration
  •Impact resistant Polycarbonate housing





#### Technical data:

Working temperature:

Capacity: illumination time 3 hours Light source 6 W POWER Stripe LED Luminosity 420 lumen Rechargeable battery: 3.6 V / 3600 mAh Battery type Li-polymer Capacity 6 Watt Charging voltage: AC 100-240 V ~ 50 / 60 Hz DC 12-24 V

	L mm	D mm	g	
450 4040	000.0	F0.0	F00	

-5° / +45°

3

4

5

6

7

8

9

10

11

12

13

14

15

16

#### Basic workshop inspection hand lamp 8 watts

- Protection pipe out of polycarbonate
- Impact resistant impact strength IK09 High quality rubber hand grip casing

- •360° revolving hooks for suspending
- With contour connector according to CEE 7/17
   Ingress protection according to IP44
- Integrated connector
- · Includes lamp



#### Technical data:

Luminosity Lamp length: 500.0 mm Connection cable length:

Cable: H05RN-F 2x1,0 mm<sup>2</sup> Operational voltage: AC 220-240 V

Protection class: Weatherproof protection:

	L mm	Ø mm	9	
550.1371	500.0	30,0	580	



#### Pro workshop inspection hand lamp 8 watts

- Industrial quality
- Double insulation
- · Protection pipe out of polycarbonate
- Impact resistant impact strength IK09
   High quality rubber hand grip casing
- Revolving hooks for suspending
  With contour connector according to CEE 7/17
- Ingress protection according to IP44
  With integrated connector
- Lamp extension tube interchangeable
- Includes lamp



#### Technical data:

8 W Lamp length: 500 0 mm Connection cable length: 5 m Cable: H05RN-F 2x1.0 mm<sup>2</sup>

Operational voltage AC 220-240 V Protection class

Weatherproof protection: IP44

	L mm	Ø mm	9	
550.1376	500.0	30,0	600	

#### Pro XL workshop inspection hand lamp 11 watts

- Industrial quality
- Double insulation
   Protection pipe out of polycarbonate
- Impact resistant impact strength IK09
   High quality rubber hand grip casing
- •Revolving hooks for suspending
- •With contour connector according to CEE 7/17
- Ingress protection according to IP54
- With integrated connector
   Lamp extension tube interchangeable
- Includes lamp



#### Technical data:

11 W Luminosity Lamp length: 630.0 mm 5 m Connection cable length:

H05RN-F 2x1,0 mm<sup>2</sup> AC 220-240 V Operational voltage: Protection class Weatherproof protection:

g
620

#### Pro XXL workshop inspection hand lamp 13 watts

- Industrial quality
- Double insulation
- · Protection pipe out of polycarbonate
- Impact resistant impact strength IK09
   High quality rubber hand grip casing
- •Revolving hooks for suspending
- With contour connector according to CEE 7/17
- Ingress protection according to IP54
- With integrated connector
   Lamp extension tube interchangeable
- · Includes lamp



#### Technical data:

13 W Luminosity 720.0 mm Lamp length: Connection cable length: 5 m H05RN-F 2x1,0 mm<sup>2</sup>

AC 220-240 V Operational voltage: Protection class

Weatherproof protection: IP54

	L mm	Ø mm	9	
550.1386	720.0	35,0	640	



### Professional XXL workshop inspection hand lamp with

- Optimum lighting
- Self-clamping and securable Span length = 1,335 1,800 mm
- Expanding bracket with large, adjustable and rubber coated hooks
- Industrial quality
- Double insulation
- Protection pipe out of polycarbonate
- Impact resistant impact strength IK09
   High quality rubber hand grip casing
- Revolving hooks for suspending
   With contour connector according to CEE 7/17
- Ingress protection according to IP54
- · With integrated connector
- · Lamp extension tube interchangeable
- Includes lamp





Technical data: Luminosity:

Adjusatbel length: 1.335-1.800 mm

Connection cable length: 5 m

Cable: H05RN-F 2x1,0 mm<sup>2</sup> Operational voltage: AC 220-240V

Protection class: IP64 Weatherproof protection:

	L mm	Ø mm	kg	
150.4305	1335-1800	74,0	2.60	

### **ACCESSORIES FOR FLASH LIGHTS**

#### Magnet holder for workshop lamps

- Universal mouting clip for workshop lamps
- •Extra large pivoting range
- Magnet completely rubberised
- Stop peg out of spring steel



	max Ø pipe mm	Ø magnetic base mm	9	
150.4219	43,0	31,0	120	
150.4219	43,0	31,0	120	

#### Workshop cable reel

- Practical and space-saving
   Extra strong, automatic return mechanism
- With endstopper
- •180° freely revolving
- Cable working length 20 m
   Connection cable 1.5 m
   Metal wall reinforcement rail 270 mm



Connection cable length:	1,5 m
Operational voltage:	230 V

		kg	
150.4320	Workshop cable reel	6.60	

17 18

19

20

21

22

23

24

25

26

27

#### **FLASH LIGHTS WITH CABLE REELS**

### Cable reel with Basic workshop inspection hand lamp

- Protection pipe out of polycarbonate
- Impact resistant impact strength IK09 High quality rubber hand grip casing
- •360° revolving hooks for suspending
- With contour connector according to CEE 7/17
   Ingress protection according to IP44
- Integrated connector
- •Includes lamp
- Includes workshop cable reel

## Cable reel with pro XL workshop inspection hand lamp

- Industrial quality
- Double insulation Protection pipe out of polycarbonate
- Impact resistant impact strength IK09
   High quality rubber hand grip casing
- •360° revolving hooks for suspending
- With contour connector according to CEE 7/17
   Ingress protection according to IP54
- With integrated connector
   Includes lamp
- •Includes cable reel 20 m



#### Technical data:

8 W Luminosity Lamp length: 500.0 mm Connection cable length: 5 m Work cable length m: 20 m

H05RN-F 2x1.0 mm<sup>2</sup> Cable: Operational voltage AC 220-240 V

Protection class: Weatherproof protection: IP44

	L mm	Ø mm	kg	
550.1370	500.0	30,0	8.08	

### Cable reel with pro workshop inspection hand lamp 8

- Industrial quality
- Double insulation
- Protection pipe out of polycarbonate
   Impact resistant impact strength IK09
- High quality rubber hand grip casing
  360° revolving hooks for suspending
- •With contour connector according to CEE 7/17
- · Ingress protection according to IP44
- With integrated connector
- •Includes lamp •Includes cable reel 20 m

#### Technical data:

11 W Luminosity 630.0 mm Lamp length: Connection cable length 5 m Work cable length m: 20 m H05RN-F 2x1,0 mm<sup>2</sup> Cable:

AC 220-240 V Operational voltage: Protection class: Weatherproof protection: IP44

	L mm	Ø mm	kg	
550.1380	630.0	35,0	8.12	

- Industrial quality
- Double insulation
- Protection pipe out of polycarbonate Impact resistant impact strength IK09
- High quality rubber hand grip casing
  360° revolving hooks for suspending
- With contour connector according to CEE 7/17
- Ingress protection according to IP54
- Includes lamp
- •Includes cable reel 20 m

## Cable reel with pro XXL workshop inspection hand lamp

- · With integrated connector



#### Technical data:

**WORK LAMPS** 

Industrial quality

•2.900 lumens luminous flux •Polycarbonate protection glass

•Impact resistant impact strength IK10

tor according to CEE 7/17
•Ingress protection according to IP54

Integrated connector
Lamp extension tube interchangeable

· Housing cover also rubber

Includes lamp
 Blow mould plastic housing

Pro workshop inspection hand lamp 36 watt

Hooks for double sided applications and with contour connec-

36 W Luminosity: Connection cable length: 5 m Operational voltage 230 V Accessory outlet: Protection class: Ш Weatherproof protection: IP54

	H mm	B mm	T mm	Spare bulb	kg
150.4255	230.0	340.0	110.0	150.4256	2.36

#### Pro workshop inspection hand lamp 72 watt

- Industrial quality
- •5.800 lumens luminous flux
   •With 2 x 230 V isolated outlet on the back
- Polycarbonate protection glass
- Housing cover also rubber
   Impact resistant impact strength IK10
- Hooks for double sided applications and pedestal with contour connector according to CEE 7/17
- Ingress protection according to IP44
- Integrated connector
- Lamp extension tube interchangeable
- Includes lampBlow mould plastic housing



#### Technical data:

Operational voltage

Luminosity 8 W Lamp length: 500.0 mm Connection cable length: 5 m Work cable length m 20 m Cable: H05RN-F 2x1.0 mm<sup>2</sup>

Protection class Weatherproof protection: IP44

	L mm	Ø mm	kg	
550.1375	500.0	30,0	8.10	

AC 220-240 V



#### Technical data:

Weatherproof protection:

Luminosity 13 W Lamp length: 720.0 mm Connection cable length: 5 m Work cable length m 20 m Cable: H05RN-F 2x1.0 mm<sup>2</sup> Operational voltage: AC 220-240 V Protection class

	L mm	Ø mm	kg	
550.1385	720.0	35,0	8.14	

IP44



#### Technical data:

Luminosity 72 W Connection cable length 5 m Operational voltage: 230 V Accessory outlet: 2 x 230 V Schuko Protection class п

Weatherproof protection: IP44

	H mm	B mm	T mm	Spare bulb	kg
150.4260	285.0	495.0	110.0	150.4261	5.02

3

#### Pro workshop inspection hand lamp 108 watt

- Industrial quality
- •8.700 lumens luminous flux
  •With 1 x 230 V isolated outlet on the back
- Polycarbonate protection glass · Housing cover also rubber
- •Impact resistant impact strength IK10
- · Hooks for double sided applications and pedestal with contour connector according to CEE 7/17
- Ingress protection according to IP44
   Integrated connector
- · Lamp extension tube interchangeable
- Includes lamp
- Blow mould plastic housing



Technical data:

108 W Luminosity: Connection cable length: 5 m 230 V Operational voltage Accessory outlet: 1 x 230 V Schuko

Protection class: Ш IP44 oroof protection

Wodinorpi	ooi protooti				
	H	B	T	Spare bulb	kg

150.4265	290.0	500.0	110.0	150.4261	5.82	

### Pro Bridgelux LED inspection hand lamp 50 watts

- Industrial quality
- •1x Bridgelux LED lamp
- •6500 Kelvin
- •Extremely impact resistant
- With contour connector according to CEE 7/17
  Waterproof according to IP65
- With integrated connector
   Corresponding to 500W halogen
- Floodlight with modern LED technology
- With mounting bracketSafety glass, transparent
- •100% luminosity without power-on delay
- •Mercury-free
- •Energy efficiency class: A •Includes lamp



#### Technical data:

Luminosity: 50 W Connection cable length: 1,5 m

H05RN-F 3x0,75 mm<sup>2</sup> Operational voltage AC 100-240 V Protection class

Weatherproof protection: IP65

	H mm	B mm	T mm	kg	
150.4385	238.0	288.0	150.0	3.10	

#### Pro Bridgelux LED inspection hand lamp 100 watts

- Industrial quality
- •1x Bridgelux LED lamp •6500 Kelvin
- Extremely impact resistant
- With contour connector according to CEE 7/17
- Waterproof according to IP65
- With integrated connector
   Corresponding to 1000W halogen
  - Floodlight with modern LED technology With mounting bracket
- Safety glass, transparent100% luminosity without power-on delay
- •Mercury-free
- •Energy efficiency class: A •Includes lamp



#### Technical data:

Luminosity 100 W Connection cable length 1,5 m

Cable H05RN-F 3x0,75 mm<sup>2</sup> Operational voltage: AC 100-240 V Protection class: Weatherproof protection: IP65

	H mm	B mm	T mm	kg
150.4390	367.0	285.0	101.0	5.60

#### Pro Bridgelux LED inspection hand lamp 150 watts

- Industrial quality
- •3x Bridgelux LED lamps
- •6500 Kelvin
- •Extremely impact resistant
- With contour connector according to CEE 7/17
   Waterproof according to IP65


- With integrated connector
  Corresponding to 1,500W halogen
  Floodlight with modern LED technology
- With mounting bracketSafety glass, transparent
- •100% luminosity without power-on delay
- Mercury-free
- Energy efficiency class: A
- Includes lamp



#### Technical data:

150 W Luminosity: Connection cable length: 1,5 m Cable H05RN-F 3x0,75 mm<sup>2</sup> Operational voltage: AC 100-240 V Protection class: Weatherproof protection: IP65

T &
B nm



#### Pro-workshop-inspection hand lamp 36 watt

- Industrial quality
- •2.900 lumens luminous flux •Polycarbonate protection glass
- · Housing cover also rubber
- •Impact resistant impact strength IK10
- With contour connector according to CEE 7/17
- Ingress protection according to IP54
- With integrated connector
- · Lamp extension tube interchangeable
- Includes lamp
- ·Blow mould plastic housing
- Fully adjustable through 2 wing screws
- •Work height 1.0 to 2.7 m
- With cable holder device
- Galvanised steel pipe
- ·3 castor wheels with special rubber tyre



#### Technical data:

36 W Luminosity: Connection cable length: 5 m Operational voltage 230 V Accessory outlet: Protection class: Ш Weatherproof protection: IP54

	H mm	B mm	T mm	Spare bulb	kg	
150.4257	230.0	340.0	110.0	150.4256	9.28	

#### consists of:

		kg	
150.4255	Pro workshop inspection hand lamp 36 watt	2.36	
150.4267	Extending tripod for work lamps	5.92	
150.4268	Castor wheel sets for 150.4267	1.00	

4

5

6

7 8

9 10

11 12

13

14

15 16

17

18

19

20

21

22

23

24

25

26

27

i



#### Professional cold light work lamp 72 watt

- Industrial quality
- •5.800 lumens luminous flux •With 2 x 230 V isolated outlet on the back
- Polycarbonate protection glass
- · Housing cover also rubber
- •Impact resistant impact strength IK10
- With contour connector according to CEE 7/17
  Ingress protection according to IP44

- With integrated connector
   Lamp extension tube interchangeable
- •Includes lamp
  •Blow mould plastic housing
- Fully adjustable through 2 wing screws
  Work height 1.0 to 2.7 m
- •With cable holder device
- · Galvanised steel pipe
- •3 castor wheels with special rubber tyre



## Technical data: Luminosity:

72 W Connection cable length: 5 m Operational voltage: 230 V Accessory outlet: 2 x 230 V Schuko

Protection class: Weatherproof protection:

	H mm	B mm	T mm	Spare bulb	kg	
150.4263	285.0	495.0	110.0	150.4261	11.94	

consists	01:		
		kg	
150.4260	Pro workshop inspection hand lamp 72 watt	5.02	
150.4267	Extending tripod for work lamps	5.92	
150.4268	Castor wheel sets for 150,4267	1.00	





#### Professional cold light work lamp 108 watt with tripod

- Industrial quality •8.700 lumens luminous flux
- With 1 x 230 V isolated outlet on the back
  Polycarbonate protection glass
- · Housing cover also rubber
- Impact resistant impact strength IK10

  With contour connector according to CEE 7/17

  Ingress protection according to IP44
- With integrated connector
- Lamp extension tube interchangeable
   Includes lamp

- Blow mould plastic housing
   Fully adjustable through 2 wing screws •Work height 1.0 to 2.7 m
- · With cable holder device
- •Galvanised steel pipe
- •3 castor wheels with special rubber tyre



#### Technical data:

108 W Luminosity: Connection cable length: 5 m Operational voltage 230 V 1 x 230 V Schuko Accessory outlet: Protection class: Weatherproof protection: IP44



#### consists of:

		kg	
150.4265	Pro workshop inspection hand lamp 108 watt	5.82	
150.4267	Extending tripod for work lamps	5.92	
150.4268	Castor wheel sets for 150.4267	1.00	

#### Professional Bridgelux LED work lamp 50Watt with tripod

- Industrial quality
- •1x Bridgelux LED lamp •6500 Kelvin
- Extremely impact resistant
- •With contour connector according to CEE 7/17
- Waterproof according to IP65
- With integrated connector
   Corresponding to 500W halogen
- Floodlight with modern LED technologyWith mounting bracket
- Safety glass, transparent
   100% luminosity without power-on delay
- \*\*Now\* luminosity without power-on delay
   \*Mercury-free
   \*Energy efficiency class: A
   \*Includes lamp
   \*Fully adjustable through 2 wing screws
   \*Work height 1.0 to 2.7 m

- With cable holder device
   Galvanised steel pipe
- •3 castor wheels with special rubber tyre



#### Technical data:

Luminosity: 50 W Connection cable length: 1.5 m Operational voltage: AC 100 - 240V / DC24V

Protection class: Weatherproof protection: IP65

		H mm	B mm	T mm	kg	
150.43	86	238.0	288.0	150.0	9.93	

#### consists of:

		kg	
150.4385	Pro Bridgelux LED inspection hand lamp 50 watts	3.10	
150.4267	Extending tripod for work lamps	5.92	
150.4268	Castor wheel sets for 150.4267	1.00	

## Professional Bridgelux LED-work lamp 100Watt with

- Industrial quality
- •1x Bridgelux LED lamp •6500 Kelvin

- Extremely impact resistant
   With contour connector according to CEE 7/17
- Waterproof according to IP65
- With integrated connector
   Corresponding to 1000W halogen
- Floodlight with modern LED technology With mounting bracket

- Safety glass, transparent
   100% luminosity without power-on delay

- \*\*Now\* luminosity without power-on delay
   \*Mercury-free
   \*Energy efficiency class: A
   \*Includes lamp
   \*Fully adjustable through 2 wing screws
   \*Work height 1.0 to 2.7 m

- With cable holder deviceGalvanised steel pipe
- •3 castor wheels with special rubber tyre



#### Technical data:

Luminosity: 100 W Connection cable length: 1,5 m

AC 100 - 240V / DC24V Operational voltage Protection class:

Weatherproof protection: IP65

	H mm	B mm	T mm	kg
150.4391	367.0	285.0	101.0	12.52

#### consists of:

001101010	0010.000 011					
		kg				
150.4390	Pro Bridgelux LED inspection hand lamp 100 watts	5.60				
150.4267	Extending tripod for work lamps	5.92				
150.4268	Castor wheel sets for 150.4267	1.00				



### Professional Bridgelux LED-work lamp 150Watt with

- •Industrial quality
  •3x Bridgelux LED lamps
  •6500 Kelvin
- Extremely impact resistant
- With contour connector according to CEE 7/17
- •Waterproof according to IP65
- With integrated connector
   Corresponding to 1500W halogen
- Floodlight with modern LED technology With mounting bracket
- Safety glass, transparent100% luminosity without power-on delay

- \*100% luminosity without power-on delay
   Mercury-free
   \*Energy efficiency class: A
   \*Includes lamp
   \*Fully adjustable through 2 wing screws
   \*Work height 1.0 to 2.7 m
- With cable holder deviceGalvanised steel pipe
- •3 castor wheels with special rubber tyre



#### Technical data:

Luminosity 150 W Connection cable length: 1.5 m Operational voltage: AC 100 - 240V / DC24V

Protection class: Weatherproof protection: IP65

	H mm	B mm	T mm	kg
150.4396	327.0	427.0	185.0	16.92

consists	01:		
		kg	
150.4395	Pro Bridgelux LED inspection hand lamp 150 watts	10.00	
150.4267	Extending tripod for work lamps	5.92	
150.4268	Castor wheel sets for 150.4267	1.00	

#### **ACCESSORIES FOR WORK LAMPS**

#### Scaffolding clamp for work lamps

- Universal scaffolding clamp for cold light work lamps
- •For all current scaffoldings and pipes up to 50 mm •Heavy and robust execution
- · Galvanised steel



	max Ø pipe mm	kg	
150.4269	50,0	1.06	

### **Extending tripod for work lamps**

- Universal tripod for work lamps
   Expandable through optional extensions
- Optimal illuminating guaranteed
- Secure stand
- Extremely compact transportation size
- On fold away tripod foot partFully adjustable through 2 wing screws

- •Work height 1,0 to 2,7 m •With cable holder device
- · Galvanised steel pipe



				_
	H mm	Castor wheel set	kg	
150.4267	1000 - 2700	150.4268	5.92	

#### Castor wheel sets for 150.4267

- •3 castor wheels with special rubber tyre
- Includes reinforcement screwWith backing plate on every castor



			kg	
150.4268	3 pcs	Castor wheel sets for 150.4267	1.00	

2 3

1

4

5

6 7

8

9 10

11 12

13

14

15

16 17

18

19 20

21

22

23

24

25

26

27

i