

3/8" Butterfly Type Air Impact Wrench, 155 NM



- loosening torque 100 NM, max. torque 155 NM after 15 seconds
- 9000 U/min
- one hand forward and reverse butterfly control
- solid and compact finish
- air consumption 85I/min









16-piece 1/2" Air Impact Wrench Kit, 366 NM



contents:

- 1/2" reversible impact wrench BSP nipple

- oil pot125 mm impact extension bar
- hex. adaptor
- 10 impact sockets

9-10-11-13-14-17-19-22-24-27 mm

- loosening torque 332 NM
- max. torque 366 NM after 15 seconds (320 NM after 5 seconds)
- air consumption 113 l/min



Item # 3223





1/2" Air Impact Wrench from # 3223, loose, 366 NM



- loosening torque 332 NM, max. torque 366 NM after 15 seconds
 air consumption 113 l/min











Air Impact Wrench 1/2", 610 NM



- extra small & light edition, weights only 1,5 kg
 air consumption 198 l/ minute
 free speed 11.000 RPM

- Hose adaptor 1/4" (nipple included)
 Sound pressure 87 DBA

3 setting options:

forward:

- Speed 1 (after 15 seconds) 180 ft.lb /245 NM
 Speed 2 (after 15 seconds) 300 ft.lb /408 NM
- Speed 3 (after 15 seconds) 450 ft.lb /610 NM reverse:
- Speed 1 (after 15 seconds) 210 ft.lb /286 NM
 Speed 2 (after 15 seconds) 340 ft.lb /462 NM
 Speed 3 (after 15 seconds) 500 ft.lb /680 NM









Air Impact Wrench 12.5 (1/2), Composite Housing, 880 NM

- very durable, suitable for daily use in workshops
- handy and well balanced
- drive: 12.5 (1/2)
- peak torque after 15 sec. 1110 Nm
 - Level 1: 200 Nm
 - Level 2: 610 Nm
 - Level 3: 880 Nm
- air consumption: min 139 I / min
- working pressure: 6.2 bar
- connector: 6,3 (1/4)
- hose inside diameter (recommended): 10 mm









Air Impact Wrench 1/2", 1085 NM

- impact mechanism: twin hammer
- max. torque: 800 FT-LB (1085Nm) free speed: 7500 R.P.M.
- air consumption: 7.4 CFM (210 l/min) hose inner diameter: 3/8" (10 mm)
- air inlet: 1/4"
- weight: 5.5 LBS (2.5kg)
- length: 6-1/2" (164 mm)
- same construction as BGS 3246













1/2" Air Impact Wrench "Powerhouse", 1355 NM

12.5 1/2

- heavy duty impact wrench for everyday workshop use
- air consumption 390l/min

- torque:

step 1: 580- 650 NM step 2: 745- 810 NM step 3: 950- 1017 NM

- max. torque after 15 seconds: 1355 NM



Item # 3233





16-piece Air Impact Wrench Set 1/2", 1355 NM

12.5 1/2

- heavy duty impact quality for workshop use
- 3 protective impact sockets in 17, 19 and 21 mm
- 125 mm extension bar
- 60 mm universal joint
- sockets: 12, 13, 14, 15, 16, 17, 18, 19, 21 and 22 mm
- Impact wrench: air consumption 390 l/h

torque:

Step 1: 580-650 NM Step 2: 745-810 NM Step 3: 950-1017 NM

max. torque after 15 seconds: 1355 NM



Item # 5259







3/4" Air Impact Wrench, 700 NM

20 🗖 ¾

- loosening torque 678 NM,
 max. torque 880 NM after 15 seconds
 3/8" BSP
- operating air pressure 6-8 bar
- air consumption 285I/min











Air Impact Wrench, 3/4", 1152 NM



- impact mechanism: Twin Hammer
- max. torque: 850 FT-LB (1152Nm) free speed: 7500 R.P.M.
- air consumption: 7.4 CFM (210 l/min)
- hose inner diameter: 3/8" (10 mm)
- air inlet: 1/4"
- weight: 5.61 LBS (2.55kg) length: 6-3/4" (170 mm) same construction as BGS 3246









3/4" Air Impact Wrench, 1355 NM



- weight 2200 g air consumption 390 l/min
- torque:

step 1: 580- 650 NM step 2: 745- 810 NM step 3: 950- 1015 NM

- max. torque after 15 seconds: 1355 NM









Air Impact Wrench, 3/4", 1762 NM



- side handle for better grip
- square drive: 3/4'
- max. torque: 1300 ft-lbs / 1762 Nm
- air pressure: 90 psi
- avg. air consumption: 6.6 cfm
- free speed: 4400 rpm air inlet: 3/8"
- weight: 6300g







1" Air Impact Wrench, 2169 NM



- air pressure: 90-115 PSI
- air consumption 380 l/min
- torque:

step 1: 1288 Nm step 2: 1762 Nm

step 3: 2033 Nm

- max. torque after 15 seconds: 2169 Nm











1" Impact Wrench, 2034 Nm

25 🛮 1

- very handy with pistol grip and side handle
- square drive: 1"
- max. torque: 2034 nm
- working air pressure: 90 psi
- max. air pressure: 100 psi air consumption: 7,0 cfm max. rpm: 5300 air inlet: 3/8"

- recommended hose: 1/2"
- max. sound level: 105,4 db/(A)
- weight: 4900 g



Item # 8497





Air Impact Screw Driver, 57 NM



- suitable for all 1/4" bits
- due to retaining mechanism the bits and adapters cannot fall out
 - drive: 1/4" inside 6-pt.
 - torque: 57 Nm

- rotation speed: 9,000 rpm length: 240 mm
- wight: 1130g
- max. working pressure: 6.2 bar air connection: 1/4"
- air consumption: 5 cfm



Item # 3293





Air Impact Wrench Set for Glow Plugs



- allows loosening of stuck glow plugs
- can also be used on screws where a low torque is required
- 4-stage torque adjustable to approx. 20-30-40-50 NM to minimize the risk of tear-off for the glow plugs
- torque setting is possible in forward and reverse rotation
- incl. 4 deep sockets in 8, 9, 10, 11 and 12 mm, 1 extension and 1 universal joint
- 1/4" drive bar
- working pressure: 6.2 bar











6.3 14

10 🗖 3/8

12.5 1 1/2

12.5 1/2

Air Ratchet, extra-short type, 30 NM

- very handy and powerful type max. torque: 22 ft-lbs (30Nm)
- max. air pressure: 90psi (6,3 bar)
- average air consumption: 3.9 CFM (110L/min)
- max. speed: 300 rpm air inlet: 1/4"
- length: 5-1/2" (140 mm) only weight: 1.1lbs (500g)



Item #	Description
8472	Air Ratchet, extra-short type, 1/4"
8473	Air Ratchet, extra-short type, 3/8"



1/4" Reversible Air Ratchet, 34 NM

- max. torque: 34 NM - free speed: 240 rpm

- length: 175 mm

- max. pressure: 6.2 bar - air consumption: 4 cfm

Item # 3234







3/8" Reversible Air Ratchet, 47 NM, stubby type

- spring-loaded ball bearing
- max. torque 34 Nm
- operating with 90 PSI length 175 mm
- air consumption 85 l/min

Item # 3239







1/2" Reversible Air Ratchet, 68 NM

- spring-loaded ball bearing
- max. torque 68 Nm
- operating with 90 PSI length 265 mm
- air consumption 113 l/min

Item # 3229







1/2" Reversible Air Ratchet, 74 NM

contents:

- 1/2" reversible ratchet
- spring-loaded ball bearing
- (operating with 90 PSI), length 250 mm 7 impact sockets 9-10-11-13-14-17-19 mm
- impact extension bar 75 mm
- 1 bit holder 75 mm
- air consumption 113 l/min













Air Ratchet Wrench, 1/2"

- special long lasting ratchet mechanism - rubber handle

- torque: 108 Nm

- free speed: 180 rpm

- max. working pressure: 6.2 bar

- air connection: 1/4"

- air consumption: 113 l/min

- weight: 1300g - length: 170 mm









Air Multi-Tool with 3 changeable Working Heads

- quick release for faster and easier change of working heads

- 3 tools in one

- 12.5 (1/2) air ratchet

- drilling maschine

- air grinder with 6 mm shank

- incl. čhuck

- working pressure: 6.3 bar

- air connection: 1/4"

- quick air coupling









Air Spot Welding Cutter

- new model with guiding lever incl. 4 drills/cutters
- air consumption 170 l/min







Item #	Description
3205	Air Spot Welding Cutter
3205-1	4-pc. Milling Cutter Set for BGS 3205



Air Nibbler

- for cutting a wide range of material up to 1mm thickness cleanly (e.g. sheet metal)
 air consumption 120 l/min





Item #	Description
3237	Air Nibbler
3237-1	Replacement Blades for Air Nibbler BGS 3237



Airbrush Gun

- adjustable spray patternfor 1/4 "air hose1.0 to 3.5 bar

- various accessories:
 - nozzle holder
 - hose
 - tanks
- nozzle diameter: 0.35 mm









Air Sander Set

- heavy duty ABS-body
- sand container can keep up to 600 cm³, can be used with brown aluminum oxide and grain sizes from 46 100 1/4" air inlet, air consumption 3,3 liter / sec.
- 5 mm steel tip







Item #	Description
3244	Air Sander Set
3244-1	Replacement Tips for Sand Blasting Gun BGS 3244





Combination Air Nailer, 50 mm

- suitable for brads 10 50 mm and narrow crown staples 16 - 40 mm
- air inlet: 1/4 npt
- max. pressure: 120 psi air consumption: 1.4 l/min with 4 bar working pressure
- operating pressure: 58 100 psi
- noise pressure: 82 db
- magazine capacity: 100 pcs.



Item # 32801





Combination Air Nailer, 32 mm

- suitable for brads 15 32 mm and narrow crown staples 16 - 32 mm
- air inlet: 1/4 npt
- max. pressure: 120 psi air consumption: 0,9 l/min under 4 bar working pressure operating pressure: 58 100 psi
- noise pressure: 78 db
- magazine capacity: 100 pcs.



Item # 32802





Air Nailer, 16 mm

- suitable for brads 6 to 16 mm
- air inlet: 1/4 npt
- max. pressure: 120 psi air consumption: 0,5 l/min under 4 bar working pressure operating pressure: 58 100 psi
- noise pressure: 82 db
- magazine capacity: 140 pcs.









Twister Gun

- for cleaning heavily soiled surfaces
- suitable for all types of mixing cleaners
- with integrated shut-off valve also suitable for drying after cleaning
- max. working air pressure: 8.5 bar
- air consumption: 310 l/min
- tank capacity: 1 litre











Air Caulking Gun, for 310 ml Cartridges

- for permanent sealing materials, adhesive paste, groove sealants etc.
- for paper, aluminum and plastic cartridges
- with pressure release, avoids material leakage
- controller for quantity adjustment









Air Spray Gun Set

- perfect for paint repairs and repainting cars, trucks, machinery and other surfaces
- includes:
- 1 HLVP spray gun for painting small surfaces cup size 125 ml, nozzle size 0.8 mm, weight 230 g
- 1 HLVP spray gun for painting large surfaces cup size 600 ml, nozzle size 1.3 mm, weight 490 g
- 1 pressure regulator with gauge
- 1 cleaning brush
- 1 multifunction wrench
- maximum pressure: 4.8 bar (70 psi)
- recommended operating pressure: 1.4 3.45 bar
- aluminium body
- air connection 1/4"









Sand Blaster Gun

- with rubber feeding hose, inner-Ø 10.5 mm
- 1/4" air connection









Air Sander Set

- perfect for all applications around the car body and all other metal surfaces
- can be used with brown aluminum oxide and grain sizes from 46 - 100
- for removing old paint, rust, dirt etc.
- 4 different caps included
- easy-to-use:
 1. fill about 1/3 of the bag with shot
 - 2. chose an appropriate cap
- connect to your air compressor
 start sandblasting

- for 1/4" air hoses working pressure: 4-12 BAR
- air consumption: 350 l/min.



	P	R	റ	+	
		**	u		
-				-	-

Item #	Description
3243-TASCHE	Sandblast Bag for BGS 3243
3243	Air Sander Set

Air Angle Drill

- suitable for working in confined spaces for e.g. drilling out broken screws on engines, etc.
- chuck size: 10 mm (3/8") length: 195 mm (7-11/16")
- air pressure: 6.2 bar (90PSI) air consumption: 105 L/min (3.7 CFM) free speed: 1.800 RPM
- air inlet: 1/4"
- hose size: 10 mm (i.d.) (3/8") weight: 0.9 kg (2.0 lbs)





7-piece Air Hammer Kit, for 10 mm round chisel

- suitable for work on car body and for mechanics
- includes:
- 4 chisel with different profiles
- quick release head
- plastic coated air hammer
- specifications:
 - strokes per minute: 3,500
- air consumption: 179 l/min
- chisel shank: round, 10 mm
- stroke: 67 mm
- working pressure: 6.2 bar
- air connection: 1/4
- length: 170 mm
- weight: 1.60 kgs
- especially suitable with Vibro Chisel Set BGS 8436











9-piece Vibro Impact Chisel Set

- ideal for loosening rusty bolts and components
- chisels have different profiles to facilitate dismantling
- using these tools has a rust-removing effect and ensures deep entering of rust removers
- suitable for ball joints, bearings, bushings, sleeves etc.
- for all air chisel with 10 mm 6-pt. and round adaptor, e.g. BGS 3515



Item # 8436



Air Needle Scaler

- ideal for removing rust and paint stroke speed: 4000 bpm air pressure: 90 psi (6.2 bar) air consumption: 7.0 cfm (198 l/min)

- air inlet: 1/4'
- weight: 4.19 lbs (1.90kgs)
- length: 13" (330 mm)









Air Tool Kit

contents:

- 1 tire inflator with gauge
- 1 blow gun
- 1 air hose
- 1 spray gun, ideal for most spray shop applications
- 1 paraffin/washing gun

All parts manufactured from aluminium diecast











Air Brake Piston Wind Back Tool

- for left- & right-side threads,
- the direction is determined by moving the angled lever at the end of the hydraulic spindle
- fits for all thread pitches
- to be used with BGS item # 1115, 1117, 1119, 1127
- 1/4" air hose adaptor















Air Car Body Saw

- free speed: 9.000 rpm/min
- length: 235 mm weigth: 770 g
- air consumption: 120 L/minute

- max. cutting capacity: 1,2 mm

- air pressure: 6,2 bar noise level: 72,0 dB (a)
- acceleration: 26,0 m/s²

Item #

3260







3 Sawing Blades for Air Body Saw Item# 3260

- one blade each 18-24-32 tooth
- made from high grade bi-metal cuts up to 1.2 mm thickness
- blade length 95 mm

Item # 3261





CV Boot Air Assembly Tool

- solid Aluminum construction
- 20-115 mm spread (adjustable)









Air "Window Seal Cutter"

- easy removal of glued car windows
- incl. screwed hose and knife 1/4" BSP
- air consumption 113 l/min









Spare Cutting Knifes for Air "Window Seal Cutter" BGS 3218

for BGS 3218 (Air Window Remover)



Item #	Description
3219	Spare Knife, straight, 52x1 mm (1 piece)
3257	2 Spare Knifes, half round, 2x24 mm, for Art. 3218
3258	2 Spare Knifes, half round, 2x36 mm, for Art. 3218





7-piece Cutting Knifes Set for Air "Window Seal Cutter" BGS 3218

- for BGS 3218 (Air Window Remover)







Air Spray Gun

- for detergent and solvent







Air Spray Gun, 1000 ccm

- for detergent and solvent







Air Paint Gun, 500 ccm

- 1.5 mm spray valve universal head: round, wide, flat









Mini Air Spray Gun, 120 ccm

- aluminium body
- chromed surface
- PP cup 120 ccm, with filter
- stainless nozzle (0.8 mm)
- air inlet: euro type quick connector







24-piece Spray Gun Cleaning Kit

- 3 large brushes
- 5 mini brushes
- 2 aluminum holders
- 6 micro needles
- 1 brass brush
- 1 large cleaning brush
- 1 plastic bottle with special lubrication fluid for air spray guns

In storing case







Air Edge Setter / Hole Punch Pliers

- length 255 mm
- stampØ 5 mm
- punches up to 1.5 mm thickness
- also suitable for stainless sheets
- air consumption 113 l/min









Air Underbody Coating Gun

- fits on all standard cartridges
- incl. flexible 600 mm air hose









Air Blow Gun with Venturi Nozzle

- the Venturi nozzle increases the air flow rate many times, making it easier to loosen dust





Air Blow Pin

- espacially suitable for small spaces
- operated by gently bending the grommet
- good handlinglength 80 mm





Air Blow Gun, Length 110 mm

- miniature finish
- adjustable blow
- with clip-holder







Air Blow Guns

- chrome plated seamless steel tubenylon fibre body with trigger1/4" PT



Item #	Description
3208	Air Blow Gun, Length 100 mm
3207	Air Blow Gun, Length 250 mm
3202	Air Blow Gun, Length 330 mm



High Performance Air Blow Gun with Venturi Nozzle

- with long steel pipe for blowing air into tight, confined spaces
- with venturi nozzle for higher air flow









Air Blow Gun, Aluminium Diecast Body

- incl. 3 tubes 25-100-200 mm







Air Blow Gun, Aluminium Diecast Body

- aluminium body







Air Eraser with Hoover Connection

- for the proper removal of stickers, adhesive residue and films on smooth surfaces and coatings
- specially designed for use on vehicles
- also for use on aluminum, metals, glass and plastic
- after working, surfaces are polished
- especially suitable for professional vehicle preparation
- with 28 and 34 mm hoover connection
- includes adaptors for:
- 110 mm abrasive cleaning fleece, 110 mm erasers and adaptation for round steel brushes
- air pressure: 90psi speed: 4000 rpm





Item #	Description
3274	Air Eraser with Hoover Connection
3274-1-1	Wire Brush 103 x 23 x 0.5, straight for BGS 3274
3274-1-2	Wire Brush 103 x 23 x 0.5, bent, for BGS 3274
3274-1-3	Wire Brush 103 x 23 x 0.7, bent, for BGS 3274
3274-2	Sanding Wheel 115 mm, for BGS 3274
3274-3	Eraser Wheel 105 x 30 x 53 mm, for BGS 3274
3274-4	Wire Brush Adapter for BGS 3274





Air Eccentric Polisher

- 150 mm velcro holder for polishing and grinding discs
- rotation speed: 10.000 rpm
- max. working pressure: 6.2 bar
- air connection: 1/4" - length: 225 mm - wight: 1900g
- air consumption: 142 l/min









Air Angle Sander

- 30, 50 and 70 mm velcro disc holder, shaft M6 x 1
- rotation speed: 14,000 rpm
- length: 185 mm
- weight: 830g
- max. working pressure: 6.2 bar
- air connection: 1/4
- air consumption: 127 l/min









170 mm Air Die Grinder Short

- heavy and robust extended air die grinder for universal use
- for contour grinding, cutting, polishing, shaping, deflashing and keying
 - capacity ¼" (6 mm)
 - shaft size 5" (127 mm)
 - free speed 22000 RPM

- required air pressure 90 PSI / 6.2 Bar air inlet 1/4" (6.3 mm)
- average air consumption: 127 l/min overall length 170 mm (6.7")
- net weight 600g









340 mm Extended Air Die Grinder

- heavy and robust extended air die grinder for universal use
- for contour grinding, cutting, polishing, shaping, deflashing and keying
 - capacity ¼" (6 mm)
 - shaft size 5" (127 mm)
 - free speed 22000 RPM

- required air pressure 90 PSI
- air inlet 1/4" (6.3 mm)
- average air consumption: 127 l/min overall length 13.4" (340 mm)
- net weight 2.90 LBS (1300g)











155 mm Air Die Grinder 90° Angle

- heavy and robust extended air die grinder for universal use
- for contour grinding, cutting, polishing, shaping,
- deflashing and keying capacity: 1/4" (6 mm) shaft size: 127

- free speed: 18,000 RPM required air pressure: 90 PSI / 6.2 BAR air inlet: 1/4"
- average air consumption: 99 l/min
- length: 155 mm - weight: 790 g









Air Separation Tool, extra long, flat Head

- cutting disc Ø 100 mm / 4" adapter Ø 16 mm
- free speed 14000 rpm
- air pressure 6.3 bar / 90 psi
- air consumption 88 L/min air inlet 1/4"
- hose size 3/8"
- length 376 mmweight only 1.44 kgsound level 84 dBA
- vibration 0.6 m/s²
- head height including spark protection 60 mm
- cutting disc available under BGS item Nr. 3266









17-piece Micro Air Grinder Kit

- 54.000 speed /min
- 1/4" air hose connection
- air consumption 0,143 m3/min
- 90 PSI air pressure required
- various grinding stones and automatic oiler included









Pistol-Grip Air Inflator

- aluminium diecast
- with flexible 400 mm hose
- gauge reads 270° (0-12 bar)











Pistol-Grip Air Inflator, calibrated

- made in Europe, calibrated operating range: 0-10 BAR
- rubber coated test gauge
- length of hose: approx. 400 mm
- scale diameter 56 mm



Item # 55400





Pistol-Grip Air Inflator with Gauge, 0-10 bar

- 50 cm tube



Item # 3242







Pistol-Grip Air Inflator, calibrated

- made in Europe, calibrated
- operating range: 0-10 BAR
- rubber coated test gauge
- Length of hose: approx. 540 mm
- scale diameter 56 mm









Tire Inflating Device, 0-11 bar

- inflating connection separate from inflating handle
- pressure gauge is protected by aluminum housing
- offset inflating nozzle
- hose between the inflating connection and housing coated with protective spring
- pressure gauge scale 0-11 bar / 0-160 psi heavy duty finish, tool weighs ca. 1180 g length of tool body ca. 260 mm














Spare Hoses with Adaptor for Air Inflators

- made in Europe
- fits BGS items 3242, 55400, 55410







Spare Hose with Adaptor for Air Inflators, 40 cm

- fits BGS items 3242, 55400, 55410



Item #	
3242-1	

PRO

Air Hose with Automatic Rewinder, 12 m, High Quality Finish

- with wall holder
- 1/4" plug
- hose diameter 8 mm / 12 mm (internal / external)
- solid metal housing





Item #	Description
3252	Air Hose with Automatic Rewinder, 12 m, High Quality Finish
3252-1	Replacement Quick Coupler for BGS 3252

Air Hose, 10 m, Internal Diameter 6 mm

- 1/4" BSP
- 20bar / 290psi maximum pressure







Spiral Air Hose, 10 m

- 1/4" air adaptor with quick release
- hose inside diameter: 8 mm
- hose outside diameter: 10 mm







Spiral Air Hose, 10 m

- 1/4" air adaptor with quick release
- hose inside diameter: 6 mm
- hose outside diameter: 8 mm







Exhaust Air Hose for Air Tools, 530 mm

- keeps dirty air away from the car
- lowers the noise level
- suitable for BGS item# 3233, 3235, 3245







Mini Oiler, 1/4" BSP







Coupling, 1/4" internal Thread

- for air hoses
- ball headed joint 360° turnable







Nipple, 1/4" external Thread

- for various air tools









1/2" Impact Wrench, 678 Nm

12.5 1½

- square drive: 1/2"

- working torque: 515 Nm - max. torque: 678 Nm - free speed: 11,000 RPM

- working pressure: 90 psi

- impact mechanism: twin hammer - air consumption Ø: 5.8 CFM - air inlet: 1/4"

- recommended hose size: 3/8"

- weight: 1.6 kg

- short, lightweight design

Item # 3245







Air Grinder / Cut Off Tool, 310 mm

- lightweight aluminum housing

- 2-component soft handle

- steel guard protects you from sparks

- lever block trigger for safety

- with rear exhaust

- cutting disc size: Ø 75 mm

- working pressure: 90 psi - air inlet: 1/4" - max. speed: 18,000 rpm

- length: 310 mm









3-in-1 Air Multi-Functional Tool

- versatile 3-in-1 air tool: Delta Sander - Saw - Scraper

- powerful operation

- perfect for working in hard to reach areas and close to corners

- triangular sanding pad: 3" (45°)

- diamond cutting disc

- air pressure: 90 psi - air inlet: 1/4" -18 NPT

- maximum oscillations: 18,000 rpm

- air consumption 6.0 cfm

- noise LpA: 86 dB(A) - LwA: 97 dB(A)

- vibration: 3,62 m/s²





Item #	Description
8580	3-in-1 Air Multi-Functional Tool
8580-2	Abrasive Pads for BGS 8580
8580-3	Scraper Set for BGS 8580
8580-4	Saw Blade for BGS 8580, offset
8580-5	Abrasive Pad Holder for BGS 8580





Air Filter/Oiler Unit with Pressure Regulator

- for filtering and oiling of compressed air
- can be screwed on a wall max. pressure: 15 bar (220 psi) air inlet and outlet: 1/4" thread
- pressure gauge adjustable 0 to 10 bar (0 150 psi)
- oil adjustable in 10 steps



Item #	
8603	





Professional Sand Blasting Gun

- perfect for all applications around the car body and all other metal surfaces
- for removing old paint, rust, dirt etc.
- can be used with brown aluminum oxide and grain sizes from #46 - #100
- easy-to-use, low consumption as tool re-uses the grit
- 4 different nozzles included
 - surface nozzle
 - inside corner nozzle
 - outside corner nozzle
 - panel spot nozzle
- aluminum cup size: 1000 c.c.
- material: aluminum alloy, enameled



Item #	Description
8593	Professional Sand Blasting Gun
8593-1	Blasting Sand 46# (Fepa 220) for BGS 8593

Air Cutter, 75 mm

- handy, short design
- adaptor for following cutting discs included: 3" Ø, 3/8" bore, 1/16" thickness free speed: 20,000 rpm

- average air consumption: 4.5 CFM
- required air pressure: 90 PSI air inlet: 1/4"
- recommended air hose: 3/8" (inside diameter)
- overall dimensions: 185 x 80 mm
- weight: 0.78 kg





Item #	Description
3286	Air Cutter, 75 mm
3286-1	Cutting Disc, 75 mm





Air Riveter

- for easy and quick riveting suitable for rivet sizes 2.4 3.2 4.0 4.8 mm
- pulling power: 720 Kg air consumption: 0.86 l/min
- stroke: 14 mm - air inlet: 1/4"
- working pressure: 6.2 bar



Item # 3284





Air Eccentric Sander

- for sanding sufaces
- with air hose and dust bag
- sanding pad: Ø 6"
- free speed: 10000 rpm sanding stroke: 5 mm air inlet: 1/4"

- air suction hose: 3/8"
- air consumption: 4.5 cfm
- working pressure: 6.3 bar
- length: 225 mm weight: 1 kg

Item # 8688





Air Paint Spray Gun

- suitable for painting car and machine parts
- aluminium body
- chromed surface
- 500 ccm cup, with filter stainless nozzle (1.4 mm)
- air inlet: Euro type quick connector max. pressure: 87 PSI
- working pressure: 30 to 43 PSI air consumption: 14.5 cfm noise level: 74.8 db(A)

- temperature range: 5 to 40°C













Air Blow Gun with Flow Regulator

- adjustable air flow
- 110 mm nozzle
- material: aluminum alloy
- air supply can be attached to handle or top of the gun
- non-slip handle
- includes 1/4" air connector
- max. pressure 10 bar, operating pressure 6.3 bar noise level: 86 dB
- air consumption: up to 320 l/min



Item # 8706







Air Blow Gun, 165 - 300 mm

- length: 165 300 mm (adjustable)
- working pressure: 6.2 8 bar (90 120 psi) max. pressure: 15 bar (217 psi)
- air inlet: 1/4"
- noise: max. 73 dBA







Air Sandblasting Cabinet, illuminated

- for sandblasting / cleaning of surfaces with e.g. dry glass beads or plastic granule abrasives
- suitable for part size up to 66 x 53 x 49 cm
- sealed cabinet with lid and viewing window, mounted gloves and cabinet air filters, to prevent the escape of abrasive material
- saves blasting material, prevents workplace contamination
- includes blasting gun and 4x different nozzle, replaceable protective film for viewing window
- working pressure: 6.2 bar
- dimensions:
- W585 x H(front 415) (rear 485) x D495 mm



Item # 8717







Retractable Air Hose Reel, 15 m

- suitable for mounting on wall, floor and ceiling
- with hose stop, auto retracting
 hose diameter: 3/8"

- hose length: 50" air inlet (F): 3/8" NPT air outlet (M): 3/8" NPT
- maximum pressure: 300PSI
- maximum air flow: 25 CFM



Item # 8584



Wire Rope Winch, 270 kg

- for mounting on boat trailer, etc.
- rope Ø: 4.2 mm
- lenght of rope: 8 m
- capacity: 270 kg (275 daN)
- gear ratio: 3.1:1

suitable for pulling loads only, not for lifting







Battery Emergency Switch, 300A

- for separating the battery from the electrical system
- is used in motor sports, construction machines
- prevents battery drain
- 2 mounting holes
- protective cap prevents entry of moisture
- incl. 2 keys with hole for operating cable







Battery Adapter, angled

- for disconnecting the battery when not used for a prolonged period
- can also by used to prevent theft of a car
- suitable for batteries with round terminals







